

Evolving technologies require linear motion rolling guides and bearing products to **perform reliably in a range** of challenging environments.

Traditionally, lubricants used in special environments, such as under vacuum, in clean environments, or at high temperatures, have utilized fluorine grease to control contamination caused by outgassing, particles and oil evaporation. And more recently, MAC grease with hydrocarbons has been used due to its excellent characteristics under vacuum.

However, these special environment greases have problems in terms of lubrication performance, heat resistance and safety, giving rise to a need for a lubricant with an excellent balance of characteristics to satisfy many requirements simultaneously.


IKO developed a new line of products with a **revolutionary liquid crystal lubricant** to meet this need. Patent pending

IKO developed the world's first **LCL Linear Way** prepacked with Liquid Crystal Lubricant which greatly improved lubrication performance with low dust generation and low evaporation properties, as well as low outgassing characteristics.

Now, IKO expanded the products available with liquid crystal lubricant. Since the structure of the lubricant is completely different from grease, it dramatically improves the performance of linear motion rolling guides and bearing products used in special environments, resulting in increased reliability.

IKO Liquid Crystal Lubricant is **neither grease nor oil. A groundbreaking innovation!**

Liquid crystal lubricants are completely different from greases composed of base oils and thickeners. They are composed only of liquid crystal compounds, **forming a completely new type of lubricant**. Conventional grease base oils lubricate using dissimilar molecules, causing difficulties with adhesion to metal surfaces and evaporation. Liquid crystal lubricant forms molecular aggregates, improving adhesion to metal surfaces and minimizing evaporation. The IKO Liquid Crystal Lubricant used in this Series provides excellent lubrication functionality, even under high contact pressure during rolling contact, which results in extremely high performance.



NIPPON THOMPSON CO., LTD. (JAPAN)

Head Office : 19-19, Takanawa 2-chome, Minato-ku, Tokyo, 108-8586, Japan
 Phone : +81 (0)3-3448-5850
 Fax : +81 (0)3-3447-7637
 E-mail : ntt@ikonet.co.jp
 URL : https://www.ikont.co.jp/eg/
 Plant : Gifu, Kamakura



IKO INTERNATIONAL, INC. (U.S.A.)

East Coast Operations (Sales Head Office)

91 Walsh Drive,
 Parsippany, NJ, 07054,
 U.S.A.
 Phone : +1-973-402-0254
 Toll Free : +1-800-922-0337
 Fax : +1-973-402-0441
 E-mail : eco@ikonet.co.jp



Midwest Operations

101 Mark Street, Unit-G,
 Wood Dale, IL, 60191,
 U.S.A.
 Phone : +1-630-766-6464
 Toll Free : +1-800-323-6694
 Fax : +1-630-766-6869
 E-mail : mwo@ikonet.co.jp

West Coast Operations

9830 Norwalk Boulevard, Suite 198,
 Santa Fe Springs, CA, 90670,
 U.S.A.
 Phone : +1-562-941-1019
 Toll Free : +1-800-252-3665
 Fax : +1-562-941-4027
 E-mail : wco@ikonet.co.jp

Silicon Valley Sales Office

1500 Wyatt Drive, Suite 10,
 Santa Clara, CA, 95054,
 U.S.A.
 Phone : +1-408-492-0240
 Toll Free : +1-800-252-3665
 Fax : +1-408-492-0245
 E-mail : wco@ikonet.co.jp

Southeast Operations

3235 Satellite Boulevard Building 400, Suite 230,
 Duluth, GA, 30096,
 U.S.A.
 Phone : +1-770-418-1904
 Toll Free : +1-800-874-6445
 Fax : +1-770-418-9403
 E-mail : seo@ikonet.co.jp

Southwest Operations

6191 N STATE HIGHWAY 161, STE 440,
 IRVING, TX 75038-2264,
 U.S.A.
 Phone : +1-972-925-0444
 Toll Free : +1-800-295-7886
 Fax : +1-972-707-0385
 E-mail : swo@ikonet.co.jp

IKO THOMPSON BEARINGS CANADA, INC.(CANADA)

731-2425, Matheson Boulevard East, 7th floor,
 Mississauga, Ontario, L4W 5K4, Canada
 Phone : +1-905-361-2872
 Fax : +1-905-361-6401
 E-mail : itc@ikonet.co.jp

IKO BRASIL SERVIÇOS EMPRESARIAIS EIRELI (BRAZIL)

Rua Frei Caneca 1407,
 Condomínio Edifício Barão de Monte Cedro,
 Cjs. 801/802, Consolação, São Paulo- SP
 Cep: 01307-909
 Phone : +55 (0)11-2366-3033
 E-mail : itb@ikonet.co.jp

NIPPON THOMPSON EUROPE B.V. (EUROPE)

The Netherlands (Sales Head Office)

Keersopstraat 35,
 3044 EX, Rotterdam,
 The Netherlands
 Phone : +31 (0)10-462 68 68
 E-mail : nte@ikonet.co.jp



Germany Branch

Mündelheimer Weg 54,
 40472 Düsseldorf,
 Germany
 Phone : +49 (0)211-41 40 61
 Fax : +49 (0)211-42 76 93
 E-mail : ntd@ikonet.co.jp

Regensburg Sales Office

Im Gewerbeplatz D 30,
 93059 Regensburg,
 Germany
 Phone : +49 (0)941-20 60 70
 Fax : +49 (0)941-20 60 719
 E-mail : ntr@iko-nt.de

U.K. Branch

2 Vincent Avenue, Crownhill,
 Milton Keynes, Bucks, MK8 0AB,
 United Kingdom
 Phone : +44 (0)1908-566144
 E-mail : sales@iko.co.uk

Spain Branch

Autovia Madrid-Barcelona, Km. 43,700
 Polig. Ind. AIDA - Nove A-8, Ofic. 2-1*
 19200-Azuqueca de Henares,
 (Guadalajara) Spain
 Phone : +34 949-26 33 90
 Fax : +34 949-26 31 13
 E-mail : nts@ikonet.co.jp

France Branch

Bâtiment le Raphaël-Paris, Nord 2,
 22 avenue des Nations
 BP54394 Villepinte
 95943 ROISSY C.D.G Cedex
 France
 Phone : +33 (0)1-48 16 57 39
 Fax : +33 (0)1-48 16 57 46
 E-mail : ntf@ikont.eu

IKO THOMPSON ASIA CO., LTD. (THAILAND)

1-7 Zuellig House, 3rd Floor,
 Silom Road, Silom, Bangrak,
 Bangkok 10500, Thailand
 Phone : +66 (0)2-637-5115
 Fax : +66 (0)2-637-5116
 E-mail : ita@ikonet.co.jp

IKO THOMPSON KOREA CO.,LTD. (KOREA)

201, Worldvision Bldg., 77-1, Yeouinaru-ro,
 Yeongdeungpo-gu, Seoul, Korea
 Phone : +82 (0)2-6337-5851
 Fax : +82 (0)2-6337-5852
 E-mail : itk@ikonet.co.jp

IKO-THOMPSON (SHANGHAI) LTD. (CHINA)

Shanghai (Sales Head Office)

1608-10, MetroPlaza No.555, LouShanGuan
 Road, ChangNing District, Shanghai,
 People's Republic of China, 200051
 Phone : +86 (0)21-3250-5525
 Fax : +86 (0)21-3250-5526
 E-mail : ntc@ikonet.co.jp

Beijing Branch

Room 1909, Tower C Oriental Media Center,
 Guanghua Road No. 4 Chaoyang District, Beijing,
 People's Republic of China, 100026
 Phone : +86 (0)10-6515-7681
 Fax : +86 (0)10-6515-7689
 E-mail : ntc@ikonet.co.jp

Guangzhou Branch

Room 834, Garden Tower, Garden Hotel
 368 Huanshi East Road, Yuexiu District, Guangzhou,
 Guangdong
 People's Republic of China, 510064
 Phone : +86 (0)20-8384-0797
 Fax : +86 (0)20-8381-2863
 E-mail : ntc@ikonet.co.jp

Wuhan Branch

Room 2300, Truroli Plaza No.72, Wusheng Road,
 Qiao kou District, Wuhan, Hubei,
 People's Republic of China, 430033
 Phone : +86 (0)27-8556-1610
 Fax : +86 (0)27-8556-1630
 E-mail : ntc@ikonet.co.jp

Shenzhen Branch

Room 1808, KEENSTAR Building 18,
 Chuangye 2nd Rd 248, Bao'an, Shenzhen, Guangdong,
 People's Republic of China, 518081
 Phone : +86 (0)755-2265-0553
 Fax : +86 (0)755-2298-0665
 E-mail : ntc@ikonet.co.jp

Xian Branch

Room 2010, Block B, Chaoyang International Plaza,
 No. 166,
 Changle West Road, Xincheng District Xi'an, Shanxi,
 People's Republic of China, 710032
 Phone : +86 (0)29-8323-5915
 E-mail : ntc@ikonet.co.jp

Qingdao Branch

Room 608, Building 47, Huarun City,
 No. 101 Shenzhen Road, Laoshan District,
 Qingdao City, Shandong
 People's Republic of China, 266100
 Phone : +86 (0)532-8670-2246
 Fax : +86 (0)532-8670-2242
 E-mail : ntc@ikonet.co.jp

Ningbo Office

Room 3406, Zhongnongxin Building, No.181,
 Zhongshan East Road, Haishu Ward, Ningbo,
 Zhejiang
 People's Republic of China, 315000
 Phone : +86 (0)574-8718-9535
 Fax : +86 (0)574-8718-9533
 E-mail : ntc@ikonet.co.jp

Shenyang Office

2-1203 Tower I, City Plaza Shenyang NO.206,
 Nanjing North Street, Heping District, Shenyang,
 People's Republic of China, 110001
 Phone : +86 (0)24-2334-2662
 Fax : +86 (0)24-2334-2442
 E-mail : ntc@ikonet.co.jp

IKO



NEW!
**Liquid Crystal
 Lubricant Series**

Linear motion rolling guides and bearing products prepacked with a **newly developed**, high-performance **liquid crystal lubricant**. Patent pending



NIPPON THOMPSON CO., LTD.

Supported Products

Linear Motion Rolling Guide Series

- Linear Way L Series
- Linear Way E Series
- Linear Way H Series
- Linear Way F Series
- Linear Roller Way Super X Series **NEW**

Note: Applicable for stainless steel models from each series.

Needle Roller Bearing Series

- Crossed Roller Bearings Series **NEW**

Availability

Liquid Crystal Lubricant Series products are made to order. Please contact IKO for more information.

Precautions for Use

- Continuous operating temperature range: 5 to 100°C (maximum operating temperature 120°C)
- The unit must be stored in a dry and clean place with low humidity and unpacked in the same environment before use as rust prevention oil has not been applied.
- The Liquid Crystal Lubricant Series is packed in clean condition and therefore cleaning or wiping down after removal from the packaging is not necessary.
- Liquid Crystal Lubricant has fluorescent properties under certain ultraviolet light.
- Use gloves when handling so that the Liquid Crystal Lubricant does not touch the skin directly.
- Respective values used in tables are for reference and are not guaranteed values.

• The specifications and dimensions of products in this catalog are subject to change without prior notice. • When these products are exported, the exporter should confirm a forwarding country and a use, and, in case of falling under the customer's requirements, take necessary procedures such as export permission application. • Although all data in this catalog has been carefully compiled to make the information as complete as possible, NIPPON THOMPSON CO., LTD. shall not be liable for any damages whatsoever, direct or indirect, based upon any information in this catalog. NIPPON THOMPSON CO., LTD. makes no warranty, either express or implied, including the implied warranty of merchantability or fitness for a particular purpose. • Reproduction and conversion without permission are prohibited.


https://www.ikont.co.jp/eg/



ISO 9001 & 14001 Quality system registration certificate

CAT-2961E

Printed in Japan © 2022.11 (AK)




The World's First!
 Improve machine performance
 with IKO Liquid Crystal
 Lubricant Series products.


Durability

Load durability (room temperature) Long-term durability exceeds 10 times that of fluorine grease at room temperature and atmospheric pressure.

[Test Conditions ①] Model Number: LWL9--B (Ball-type Linear Motion Rolling Guide)
 Speed: 1m/s
 Load: 181N




[Test Conditions ②] Model Number: LRXD20SL (Roller-type Linear Motion Rolling Guide)
 Speed: 1m/s
 Load: 1150N



Load durability (high temperature) 2 to 6 times greater durability than other types of grease.



[Test conditions] Model Number: LWL18--B Speed: 1m/s Temperature: 120°C
 Load: 114N Evaluation: Traveling distance until insufficient lubrication occurs



Clean Environment


Outgas properties The outgas properties in high vacuum environments show excellent performance even at high temperatures.

[Measuring Conditions] Vacuum Degree: 10⁻⁵Pa Status: Liquid Crystal Lubricant Only



Low dust-generation properties Dust generation is less than 1/10 of lithium soap based grease.


[Test conditions] Model Number: LWL9--B/N Load: 80N Speed: 1m/s
 Evaluation Time: 45hr Measured Particle Size: 0.5µm or more




Lubrication Performance

Rolling resistance The rolling resistance is lower than that of fluorinated grease or lithium soap based grease.

[Test Conditions] Model Number: LWL9--B/N (Ball-type Linear Motion Rolling Guide)



[Test Conditions] Model Number: LRXSG20 (Roller-type Linear Motion Rolling Guide)



Evaporation characteristics There is zero mass loss even at 100°C. Liquid Crystal Lubricants have no loss due to evaporation.

[Test conditions] Atmosphere: Air Temperature: 100°C Time: 770 hr

